

CASES
1550
Case



1550 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1550 Case Configurations

Cat. #	Description
1550	1550 Case
1550NF	1550 Case (No foam)
1554	1550 Case with Padded Dividers



Black



Silver



Orange



Yellow



Desert Tan

1550 Case Specifications

Exterior Dimensions (L x W x D)

20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)

Lid Depth

1.75" (4.4 cm)

Weight with foam

11.9 lbs. (5.4 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

18.43" x 14.00" x 7.62" (46.8 x 35.5 x 19.3 cm)

Bottom Depth

5.87" (14.9 cm)

Total Depth

7.62" (19.3 cm)

Weight without foam

10.58 lbs. (4.8 kg)

Buoyancy Max.

69.89 lbs.
(31.7 kg)

Personalized Nameplate Available

1550 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1550 Case Accessories

Cat. #	Description
1550PF	Special Application Panel Frame
1551	4 pc. Replacement Foam Set
1552	Pick N Pluck™ Sections Only (set of 2)
1553	Replacement O-ring
1555	Padded Divider Set Only

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com