


Part No.

# QTHP-KIT1-GP

*QTHP hydraulic pump, 1000 psi/7 Mpa digital gauge, 3ft hose, 1/4" MNPT adapter, zippered bag*

Calibration kit with pump and digital pressure gauge



QTHP-KIT1-GP

## Included Items

- Hand Pump - QTHP Hydraulic Hand Pump (QTHP)
- Pressure Reference - LC10 pressure gauge, 1000 psi / 70 bar / 7 MPa, 1/4" Male NPT bottom connection (LC10-GP2M)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Case - QTHP, XTHP Hand Pump Carrying Case (QTHP-0275)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

## Hand Pump QTHP

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Fine Adjustment Resolution	0.01 PSI / 0.07 mbar / 0.00 kPa
Materials	Anodized Aluminum, Brass, Stainless Steel, Polysulfone
Max Operating Temperature	140 °F / 60 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Petroleum Based Oil, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil
Min Operating Temperature	-29 °F / -34 °C
Outlet Port	Male Quick-test, Male Quick-test

## Hand Pump QTHP

Pressure Media	Liquid
Reservoir Volume	4.2 fl. oz
Seal Materials	Buna-N, Teflon
Weight	2.93 lbs / 1.33 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 10.6 in (26.92 cm)

## Pressure Reference LC10-GP2M

Battery Count	2
Battery Life	1500 Hours
Battery Type	AA Alkaline (IEC-LR6)
Burst Pressure	4000 PSI / 275 bar / 28 MPa
Calibration Certificate	Not included
Certifications	Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
Country of origin	USA
Electrical Rating	50 mA @ 5 VDC
Engineering Units	atm, bar, cmH <sub>2</sub> O @4°C, inH <sub>2</sub> O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm <sup>2</sup> , mmHg @0°C, Torr, ftH <sub>2</sub> O @39°F, cmHg @ 0°C, oz / sqin
Ingress Protection	IP67 (1 meter water submersion for 30 minutes)
LCD Display	2.4 in / 61 mm segmented LCD Display
Materials	ABS / Polycarbonate Blend, Powder Coated Aluminum
Max Operating Temperature	120 °F / 50 °C
Max Pressure	1000 PSI / 70 bar / 7.00 MPa
Max Storage Temperature	165 °F / 75 °C
Measurement Type	Gauge Pressure
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	-4 °F / -20 °C
Min Storage Temperature	-40 °F / -40 °C
Operating Altitude (max)	10,000 ft (3050 m)
Pressure Measurement Uncertainty	+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Process Connection	1/4" Male NPT (ASME B1.20.1)
Process Connection Location	Bottom mount
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
Sensor Type	Pressure Sensor

### Pressure Reference LC10-GP2M

USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)

### Reference Connection QTHA-2FBA

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Wrench Size	3/4 In 19 mm
Dimensions	H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm)

### Process Connection QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

### Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass

**Hose** QTQT-HOS-3ft

Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

**Bag** SM-0084

Max Pressure	0.00 PSI / 0.00 mbar / 0.00 kPa
Max Vacuum	0.00 InHg / 0.0 kPa
Materials	Zippered Nylon
Country of origin	USA