

CASES 1650 Case



1650 Case

- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dust proof

1650 Case Configurations

| Cat. # | Description |
|--------|--------------------------------|
| 1650 | 1650 Case |
| 1650NF | 1650 Case (No foam) |
| 1654 | 1650 Case with Padded Dividers |



1650 Case Specifications

Exterior Dimensions (L x W x D)

31.59" x 20.47" x 12.45" (80.2 x 52 x 31.6 cm)

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth

1.81" (4.6 cm)

Weight with foam

28.06 lbs. (12.73 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

28.57" x 17.52" x 10.65" (72.5 x 44.5 x 27 cm)

Bottom Depth

8.84" (22.4 cm)

Total Depth

10.65" (27 cm)

Weight without foam

24.03 lbs. (10.9 kg)

Buoyancy Max.

181 lbs.
(82.1 kg)

No. of Wheels

4

Personalized Nameplate Available

1650 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1650 Case Accessories

| Cat. # | Description |
|--------|--|
| 1651 | 4 pc. Replacement Foam Set |
| 1652 | Pick N Pluck™ Sections Only (set of 2) |
| 1653 | Replacement O-ring |
| 1655 | Padded Divider Set Only |
| 1659 | Photo/Lid Organizer for 1650 Case |

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com