

Part No.

QTHA-KIT31-SS

Ralston Quick-test Fractional Tube Fitting Kit, Stainless Steel

Connect to multiple sizes of fractional tube fittings for testing using a Ralston Quick-test hose



QTHA-KIT31-SS

Included Items

- 1/8" Tube - 1/8" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-1TS0-QD)
- 1/4" Tube - 1/4" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-2TS0)
- 3/8" Tube - 3/8" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-3TS0)
- 1/2" Tube - 1/2" tube fitting x male Quick-test, no check-valve, S.S. (QTHA-4TS0)
- Hose - Quick-test 6900 psi hose, S.S. hose ends, 3 ft (92 cm) long (QSQS-HOS-3ft)
- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)

Specs/Attributes

Weight	10.93 oz / 310 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 1 in (2.54 cm)

1/8" Tube QTHA-1TS0-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N

1/8" Tube QTHA-1TS0-QD

Connector End 1	1/8" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.82 oz / 52 grams
Dimensions	H: 1.65 in (4.19 cm) x W: 0.78 in (1.98 cm) x D: 0.78 in (1.98 cm)

1/4" Tube QTHA-2TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Connector End 1	1/4" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	1.06 oz / 30 grams
Dimensions	H: 1.47 in (3.73 cm) x W: 0.56 in (1.42 cm) x D: 0.56 in (1.42 cm)

3/8" Tube QTHA-3TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Connector End 1	3/8" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	9.19 lbs / 4.17 kg
Dimensions	H: 1.53 in (3.89 cm) x W: 0.72 in (1.83 cm) x D: 0.72 in (1.83 cm)

1/2" Tube QTHA-4TS0

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C

1/2" Tube QTHA-4TS0

Seal Materials	Buna-N
Connector End 1	1/2" Male Tube Fitting
Connector End 2	Male Quick-test
Weight	2.66 oz / 75 grams
Dimensions	H: 1.7 in (4.32 cm) x W: 1 in (2.54 cm) x D: 1 in (2.54 cm)

Hose QSQS-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT
Weight	2.48 oz / 70 grams

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6.5 in (16.51 cm) x W: 6.5 in (16.51 cm) x D: 0.5 in (1.27 cm)